### **CE-MARKING**



1922

Emülzer Asfaltevi Tecrit Maddeleri San. Tic. Ltd. Şti.

DOP-772/773/774 15651-1 F EXT-INT-CC 15651-4 PW-EXT-INT-CC

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYİ VE TİCARET LİMİTED ŞİRKETİ













### **DECLARATION OF PERFORMANCE**

DOP -772/773/774

1. Unique identification code of the product-type:

Emulseal PU Mastic 40

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

BATCH NUMBER: SEE PRODUCT PACKAGING

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

SEALANT FOR FAÇADE ELEMENTS : EN-15651-1: F-EXT-INT-CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SAN. VE TİC. LTD ŞTİ. Barbaros Hayrettin Paşa Mah. Cebeci Caddesi No: 73 Küçükköy/Gaziosmanpaşa/İstanbul

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

NOT RELEVANT

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

SYSTEM 3; SYSTEM 3 FOR REACTION TO FIRE

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 15651-1

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

NOT RELEVANT

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYİ VE TİCARET LİMİTED ŞİRKETİ











# 9. Declared performance

CONDITIONING: PROCEDURE A (ACCORDING TO ISO 8340)

SUBSTRATE: Mortar /Glass

Essential Characteristic	Declared Performance	Harmonized Standard
Reaction to Fire	Class E	-
Resistance to flow	≤3 mm	EN 15651-1
Loss of Volume	≤10%	EN 15651-1
Tensile Properties after immersion in water	No Failure	EN 15651-1
Tensile Properties	>0,4	EN 15651-1
Tensile properties for non- structural sealants used in cold climates	>0,6	EN 15651-1
Tensile Properties at maintained extension	No Failure	EN 15651-1
Adhesion/Cohesion at variable temperatures	No Failure	EN 15651-1
Durability	Pass	EN 15651-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General Manager

Istanbul,2014

Signature

EMÜLZER ASFALTEVI FECRIT MADDELERI SANAVI VETİCARET LİMITED SİRRETİ Cebeci Caddeli No. 73 Kıçılıklığı 1100 İstanbul Tel: +90 (212) 537 2500 Fols-490 (212) 617 23 80 Küçlikley V.D. 3340058386

EMÜLZER ASFALTEVİ TECRİT MADDELERİ ŞANAYİ VE TİCARET LİMİTED ŞİRKETİ











### **DECLARATION OF PERFORMANCE**

DOP -772/773/774

1. Unique identification code of the product-type:

**EMULSEAL PU 40** 

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

BATCH NUMBER: SEE PRODUCT PACKAGING

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

SEALANT FOR FAÇADE ELEMENTS: EN-15651-4: PW-EXT-INT-CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SAN. VE TİC. LTD ŞTİ. Barbaros Hayrettin Paşa Mah. Cebeci Caddesi No: 73 Küçükköy/Gaziosmanpaşa/İstanbul

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**NOT RELEVANT** 

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

SYSTEM 3; SYSTEM 3 FOR REACTION TO FIRE

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 15651-4

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**NOT RELEVANT** 

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYİ VE TİCARET LİMİTED ŞİRKETİ











## 9. Declared performance

CONDITIONING: PROCEDURE A (ACCORDING TO ISO 8340)

SUBSTRATE: Mortar

Essential Characteristic	Declared Performance	Harmonized Standard
Reaction to Fire	Class E	-1
Resistance to flow	≤3 mm	EN 15651-4
Loss of Volume	≤10%	EN 15651-4
Tensile Properties at maintained extension	No Failure	EN 15651-4
Tensile Properties at maintained extension-Cold climate	No Failure	EN 15651-4
Tear resistance	No failure	EN 15651-4
Tensile Properties after immersion in water	No Failure	EN 15651-4
Tensile Properties after immersion in salt water	No Failure	EN 15651-4
Tensile Properties	>0,4	EN 15651-4
Tensile properties for non- structural sealants used in cold climates	>0,6	EN 15651-4
Durability	Pass	EN 15651-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General Manager

Istanbul, 2014

Signature

EMÜLZER ASFALTEVI TEÇKİR MADDELERİ SANAYİ VE TİÇARET İLİMİFED SİLKETİ Cebeci Caddesi No. 73 Küçükköy 341 qolktanbul Tel: +90 (212) 537 2500 Faks: +90 (212) 617 23 80 Küçükköy V.D. 3840058386

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYI VE TİCARET LİMİTED ŞİRKETİ











